

The logo for Caprari, featuring the word "caprari" in a bold, lowercase, sans-serif font, enclosed within a white rectangular border.

pumping power

NC ISO

ISO 2858 Standard Single Stage
Centrifugal Pumps

NC ISO

Flow Rates to 280 lps (1,000 m³/hr)

Head Pressures to 160 metres

Operation Conditions:

Temperature range: - 40 deg C to +140 deg C*

* Special mechanical seal required above 120 deg C

Pressure Rating: PN16 & PN24**

** PN24 Special Request

Sealing Arrangement: Gland Packed or Mechanical Seal***

*** Mechanical Seal Standard

Flow Rates: up to 280 lps (1,000 m3/hr)

Head Pressures: up to 160 metres

Impeller Materials: Bronze or Cast Iron

Maximum Speed: up to 3500 rpm****

**** Dependant on Model

APPLICATIONS:

Agriculture

Fire

Irrigation

Industry

Water Treatment

Mining

Aquaculture

Water Transfer

Water Supply

Booster Stations

Cooling Towers

Wash Down

Dust Suppression

Air Conditioning

Water Circulation

Pools

Water Features



Caprari Pumps Australia

3 Jeanes Street
BEVERLEY SA 5009

Ph: +61 8 8244 4442

Email: sales@caprari.com.au

caprari

www.caprari.com.au



iPumpMobile